

# L300 Tack Tank

**LeeBoy**



Perfect for the all-inclusive commercial paving contractor, the L300 Tack Distributor provides a perfectly sized tank for small to large projects including parking lots, patching, driveways or soil stabilization. Daily task can be completed with ease by relying on the trouble-free Honda powered engine and the proven reliable user-friendly design. Uniquely configurable, the customizable options give the contractor the ability to create a solution specific to their exact needs.

## Performance Features:

- 300 Gallon (1,136 l) Capacity Tank
- 4.8 hp (3.6 kw) Honda Engine
- 6' (1.8 m) Wand with On/Off Valve
- 40' (12.19 m) Heavy-Duty Recoil Hose Reel
- 4,400 lbs (1,996 kg) Loaded Weight
- 1" (25 mm) Rear Tank Sampling Valve
- One 300,000 BTU Propane Burner
- Trailer-Mounted Configuration
- Electric brakes
- Emergency Brake-Away System
- Optional Accessories Available



# L300 Tack Distributor Specifications



Tank Size	300 gallons (1,136 l)
Dimensions (Trailer Configuration)	<ul style="list-style-type: none"> <li>- Length: 12' 1" (3.68 m)</li> <li>- Width: 6' 4" (1.94 m)</li> <li>- Height: 5' 9" (1.76 m)</li> <li>- Shipping Weight: 1,950 lbs (885 kg)</li> </ul>
Engine	Honda – 4.8 hp (3.6 kw)
Capacities	- Fuel: 1 gallon (3.79 l)
Tank Dimensions	<ul style="list-style-type: none"> <li>- Length: 52" (1.32 m)</li> <li>- Width: 54.125" (1.37 m)</li> <li>- Height: 36.25" (.92 m)</li> </ul>
Asphalt Pump	- Specially designed 7 gallons per minute (26.5 lmp) pump
Heat System	<ul style="list-style-type: none"> <li>- One 300,000 BTU propane burner</li> <li>- One start burner</li> <li>- 40 lbs (18.1 kg) propane fuel tank</li> </ul>
Temperature Gauge	<ul style="list-style-type: none"> <li>- 50 - 300° F (10 - 149° C)</li> <li>- Adjustable angle faceplate</li> </ul>
Flush Tank	- 7 gallons (26.5 l) tank with suck back valve
Hose and Reel	- .5" x 40' (13 mm x 12.19 m) heavy-duty recoil hose reel

Wand	<ul style="list-style-type: none"> <li>- 6' (1.829 m) wand with cold handles</li> <li>- On/off valve</li> <li>- Removable spray tip</li> </ul>
Manhole	<ul style="list-style-type: none"> <li>- 20" (508 mm) diameter</li> <li>- 10" (254 cm) diameter fill hole</li> <li>- 3 psi (2.1 bar) pressure relief</li> </ul>
Clean Out	- 4" (102 mm)
Sampling Valve	- 1" (25 mm)
Optional Equipment	<p><b>Engines</b></p> <ul style="list-style-type: none"> <li>- Honda gas - 4.8 hp (3.6 kW) electric start</li> <li>- Hatz diesel - 7.2 hp (5.4 kW) pull start or electric start</li> <li>Fuel: 1.32 gallons (5.0 l)</li> </ul> <p><b>Heat Systems</b></p> <ul style="list-style-type: none"> <li>- Diesel Burner</li> <li>One 300,000 BTU diesel burner (only available with electric start engines)</li> <li>7 gallon (26.5 l) fuel tank</li> <li>Auto ignition diesel burner with outfire</li> <li>- Overnight Heat</li> <li>120 volt/1500 watt</li> <li>Immersion element</li> </ul> <p><b>Spray bar</b></p> <ul style="list-style-type: none"> <li>Width: 8' (2.44 m)</li> <li>Controls: In-truck controls (requires 8' spray bar option)</li> </ul> <p><b>Insulated Tank</b></p> <ul style="list-style-type: none"> <li>2" ball hitch</li> <li>Waste bucket mount option</li> </ul>



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300  
 For additional products or information, visit our website: [www.LeeBoy.com](http://www.LeeBoy.com)

All trademarks identified by ® or ™ are registered trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and product development. © 2019 ST Engineering LeeBoy, Inc. All rights reserved. BR-4004.1-EN

