

L600 Tack Tank

LeeBoy



Image Coming Soon

Perfect for the all-inclusive commercial paving contractor, the L600 Tack Distributor provides a perfectly sized tank for larges projects including parking lots, patching, driveways or soil stabilization. Daily tasks can be completed with ease by relying on the trouble-free Honda powered engine and the proven reliable user-friendly design. Uniquely configurable, the customizable options give the contractor the ability to create a solution specific to their exact needs.

Performance Features:

- 600 Gallon (2,271 l) Capacity Tank
- 4.8 hp (3.6 kw) Honda Engine
- 6' (1.8 m) Wand with On/Off Valve
- 40' (12.19 m) Heavy-Duty Recoil Hose Reel
- 7,270 lbs (3,298 kg) Loaded Weight
- 1" (25 mm) Rear Tank Sampling Valve
- One 300,000 BTU Propane Burner
- Trailer-Mounted Configuration
- Electric brakes
- Emergency Brake-Away System
- Optional Accessories Available



L600 Tack Distributor Specifications



Tank Size	600 gallons (2,271 l)
Dimensions (Trailer Configuration)	<ul style="list-style-type: none"> - Length: 15' 8" (4.78 m) - Width: 6' 4" (1.94 m) - Height: 5' 9" (1.76 m) - Shipping Weight: 3,050 lbs (1,370 kg)
Engine	Honda – 4.8 hp (3.6 kw)
Capacities	- Fuel: 1 gallon (3.79 l)
Tank Dimensions	<ul style="list-style-type: none"> - Length: 97.875" (2.48 m) - Width: 54.125" (1.37 m) - Height: 36.25" (.92 m)
Asphalt Pump	- Specially designed 7 gallons per minute (26.5 lmp) pump
Heat System	<ul style="list-style-type: none"> - One 300,000 BTU propane burner - One start burner - 40 lbs (18.1 kg) propane fuel tank
Temperature Gauge	<ul style="list-style-type: none"> - 50 - 300° F (10 - 149° C) - Adjustable angle faceplate
Flush Tank	- 7 gallons (26.5 l) tank with suck back valve
Hose and Reel	- .5" x 40' (13 mm x 12.19 m) heavy-duty recoil hose reel

Wand	<ul style="list-style-type: none"> - 6' (1.829 m) wand with cold handles - On/off valve - Removable spray tip
Manhole	<ul style="list-style-type: none"> - 20" (508 mm) diameter - 10" (254 cm) diameter fill hole - 3 psi (2.1 bar) pressure relief
Clean Out	- 4" (102 mm)
Sampling Valve	- 1" (25 mm)
Optional Equipment	<p>Engines</p> <ul style="list-style-type: none"> - Honda gas - 4.8 hp (3.6 kW) electric start - Hatz diesel - 7.2 hp (5.4 kW) pull start or electric start Fuel: 1.32 gallons (5.0 l) <p>Heat Systems</p> <ul style="list-style-type: none"> - Diesel Burner One 300,000 BTU diesel burner (only available with electric start engines) 7 gallon (26.5 l) fuel tank Auto ignition diesel burner with outfire - Overnight Heat 120 volt/1500 watt Immersion element <p>Spray bar</p> <ul style="list-style-type: none"> Width: 8' (2.44 m) Controls: In-truck controls (requires 8' spray bar option) <p>Insulated Tank</p> <ul style="list-style-type: none"> 2" ball hitch Waste bucket mount option



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
 For additional products or information, visit our website: www.LeeBoy.com

All trademarks identified by ® or ™ are registered trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and product development. © 2019 ST Engineering LeeBoy, Inc. All rights reserved. BR-4004.1-EN

