



OIL-JACKETED MELTING KETTLES WITH ELECTRICALLY HEATED HOSE SYSTEM



KERA180BRE

Available Sizes: 180 gal | 230 gal | 370 gal

Marathon's KERA models are designed for high production crack filling of hot poured rubberized crack sealant. These diesel fired kettles feature an electrically heated hose delivery system that is capable of heating, melting and applying rubberized crack sealant, not requiring any additional equipment!

FEATURES

- Manufactured with minimum 10 GA steel, fully welded and constructed of heavy duty 6" channel and gusseted in locations for safety and strength.
- Diesel powered burner & 23hp liquid cooled Kohler diesel engine for maximum efficiency!
- Diesel burner controlled by an Automatic Digital Temperature Control System that controls oil and sealant temperatures
- Reverse loading anti-splash door(s) located curbside, for safe and easy loading of material.
- 110V 1,500W Overnight heater maintains heat to reduce daily start-up time.
- Recirculation port for quicker start-up and material recirculation
- 3,000W Watt generator heats hose, as well as provides convenient on-side 120 VAC power source.
- Fully insulated with ceramic fibre insulation to minimize heat loss.

SPECS

| Models | KERA180BRE | KERA230BRE | KERA370BRE |
|--------------------|---|---|---|
| Shipping Weight | 4,340 lbs (1,969 kg) | 4,936 lbs (2,239 kg) | 6,533 lbs (2,963 kg) |
| Dimensions | | | |
| Overall Length | 187" | 201" | 221" |
| Overall Width | 80" | 80" | 80" |
| Overall Height | 84" | 86" | 91" |
| Loading Height | 52" | 54" | 57" |
| Capacity | | | |
| Material Vat | 180 gal (681 L) | 230 gal (870 L) | 370 gal (1,400 L) |
| Heat Transfer Oil | 30 gal (113 L) | 35 gal (132 L) | 55 gal (208 L) |
| Diesel Fuel Tank | 30 gal (113 L) | 30 gal (113 L) | 30 gal (113 L) |
| Hydraulic Oil Tank | 13 gal (49 L) | 13 gal (49 L) | 13 gal (49 L) |
| Engine | | | |
| | 23hp Liquid cooled, electric start, Kohler diesel | 23hp Liquid cooled, electric start, Kohler diesel | 23hp Liquid cooled, electric start, Kohler diesel |
| Burner | | | |
| | (1) 324,000 BTU diesel burner | (1) 324,000 BTU diesel burner | (2) 324,000 BTU diesel burners |
| Suspension | | | |
| Axle(s) | Tandem | Tandem | Tandem |
| Capacity | 7,000 lbs (3,175 kg) | 10,400 lbs (4,717 kg) | 14,000 lbs (6,350 kg) |
| Tires -size | (4) 205/75/R15 | (4) 225/75/R15 | (4) 235/85/R16 |

***Specifications subject to change without notice.**

OPTIONS

- 80 CFM Vanair Compressor with 40' air hose
- Hot Air Lance installed with hoses
- Hydraulic surge braking system
- Green strobe burner indicator light
- Amber strobe light
- Flashing arrow stick with LED arrow ends
- 2-5/16" ball hitch
- Spare tire and rim mounted

KERA180BRE with optional 80 CFM Vanair Compressor

