



OIL-JACKETED MELTING KETTLES WITH OIL HEATED HOSE SYSTEM



KERA 130HD

Available sizes: 130 gal | 230 gal

Marathon's KERA models are designed for high production crack filling of hot poured rubberized crack sealants. These diesel fired kettles feature an oil heated hose delivery system that is capable of heating, melting and applying rubberized crack sealant, not requiring any additional equipment!

FEATURES

- Manufactured with minimum 10 GA steel, fully welded and constructed of heavy duty 5" channel and gusseted in locations for safety and strength.
- Diesel powered burner & 23hp liquid cooled Kohler diesel engine for maximum efficiency!
- Diesel burner controlled by an Automatic Digital Temperature Control System that controls oil and sealant temperatures.
- Reverse loading, anti-splash door(s) located curbside, for safe and easy loading of material.
- 110V 1500W Overnight heater maintains heat to reduce daily start-up time.
- Fully insulated with ceramic fibre insulation to minimize heat loss.

SPECS

Models

KERA130HD

KERA230HD

Shipping Weight

4,095 lbs (1,857 kg)

5,118 lbs (2,321 kg)

Dimensions

Overall Length

182"

205"

Overall Width

80"

80"

Overall Height

82"

90"

Loading Height

46"

52"

Capacities

Material Vat

130 gal (492 L)

230 gal (870L)

Heat Transfer Oil

30 gal (113 L)

35 gal (132 L)

Diesel Fuel Tank

30 gal (113 L)

30 gal (113 L)

Hydraulic Oil Tank

22 gal (83 L)

22 gal (83 L)

Engine

23hp Liquid cooled,
electric start, Kohler diesel

23hp Liquid cooled,
electric start, Kohler diesel

Burner

(1) 324,000 BTU diesel burner

(1) 324,000 BTU diesel burner

Suspension

Axle(s)

Tandem

Tandem

Capacity

7,000 lbs (3,175 kg)

10,400 lbs (4,717 kg)

Tires -size

(4) 205/75/R15

(4) 225/75/R15

***Specifications subject to change without notice.**

OPTIONS

- 80 CFM Vanair Compressor with 40' air hose
- Hot Air Lance installed with hoses
- Hydraulic surge braking system
- Green strobe burner indicator light
- Amber strobe light
- Flashing arrow stick with LED arrow ends
- 2-5/16" ball hitch
- Spare tire and rim mounted
- 2" Gravity pour valve