

# HOT AIR LANCE



# HAL

The Marathon Hot Air Lance is a high temperature, high velocity, hot air lance that will easily dry moisture from the pavement allowing the operator to crack seal much faster! This process is ideal for the preparation of crack sealing because it allows for superior adhesion of the crack sealant into the asphalt. This process extends the life of the repair for years to come!

# **FEATURES**

#### **Torch**

 All stainless steel construction, air valve, propane valve, deflector assembly and adjustable shoulder strap.

#### **Air Hose**

- 3/4" x 40 ft hose with Chicago quick disconnect & compressor fittings. Hose is wrapped in protective cover to minimize damage.
- 3/8" 41' Propane hose comes equipped with vapour propane regulator & protective hose cover to minimize damage.

#### **Propane Consumption**

• 5.57 lbs/hr at 20 psi

#### **Propane Supply**

20 psi (use min 100 lb-vapour withdrawal tank)

# **SPECS**

Compressed Air Consumption 80 CFM at 100 psi

Torch Length 47 1/2"

Torch Weight 11 lbs (5 kg)

Air Output Temperature 2500°F

BTU Rating 150,000 BTU/hr

Propane Supply 20 psi (use min 100 lbs - vapour withdrawal tank)

Propane Consumption 5.57 lbs/hr at 20 psi

# **OPTIONS**



# **Wheel Kit**

Our Marathon wheel kit is an excellent accessory to add to your Hot Air Lance. This kit provides easy maneuverability and helps to deflect flying debris.



# Viper Gas Rotary Screw Air Compressor

### **Gas-Powered Transportability**

The Viper air compressor provides mobile power when and where you need it, with the flexibility of a gas-powered rotary screw air compressor. The Viper offers heavy-duty power, on or off your truck bed and gives you the flexibility only a transportable unit can offer.