

TUBE FIRED HOT TACK SPRAYERS



TPS250PT

Available sizes: 115 gal | 250 gal | 500 gal

Marathon's hot tack sprayers provide a fast and reliable means of heating and applying bituminous emulsions and tack coats. Our units are capable of heating a large volume of bitumen on a steady basis and offer many operator friendly features and options.

FEATURES

- Manufactured with 10 GA steel for a long service life.
- All sizes are available in both skid and trailer mount.
- Standard models come with a 5hp engine and a 10 GPM pumping system.
- Electric brakes and breakaway kits come standard on all trailer mounted equipment.
- 10" diameter vented flip-top filler lid for fast material filling.
- A 5' spray wand and 50' material hose comes mounted on a heavy duty hose reel.
- Units are equipped with a large 10 gallon solvent tank for easy clean out and a 2" material dispensing valve.

SPECS

All "TPS" models maximum operating temperature is 200°F

Model	TPS115S	TPS250PT	TPS500PT
Shipping Weight	619 lbs (280 kg)	1,407 lbs (638 kg)	2,583 lbs (1,172 kg)
Overall Length	44"	134"	166"
Overall Width	56"	72"	80"
Overall Height	45"	68"	74"
Loading Height	25"	47"	54"
Capacities	115 gal (435 L)	250 gal (946 L)	500 gal (1,892 L)
Engine	5hp	5hp	5hp
Pump	10 GPM	10 GPM	10 GPM
Burner	(1) 80,000 BTU vapour propane	(2) 80,000 BTU vapour propane	(2) 80,000 BTU vapour propane
Axle(s)	N/A	Single	Tandem
Capacity	N/A	5,200 lbs (2,359 kg)	(2) 5,200 lbs (4,718 kg)
Tires -size	N/A	(2) 225/75/R15	(4) 225/75/R15

***Specifications subject to change without notice.**

OPTIONS

- 6' spraybar with 18 GPM pumping system and operator's platform
- 8' folding spraybar with 18 GPM pumping system and operator's platform
- Air operated ball valve with cab control and compressor (for spraybar option)
- 185,000 BTU vapour propane hand torch with 15' hose
- Flashing arrow board with LED arrow ends
- 12 gallon waste/recovery tank
- Hydraulic braking system
- Amber strobe light
- 2-5/16" Ball hitch