

DIESEL FIRED OIL-JACKETED MELTING KETTLES WITH GRAVITY POUR DELIVERY SYSTEM



UCMK370DT

Available sizes: 130 gal | 230 gal | 370 gal

Marathon's gravity fed units are capable of heating, melting and dispensing hot applied rubberized material for crack sealing, waterproofing, and roofing. Available as one single fuel source, making them more efficient and economical to run.

FEATURES

- Manufactured with minimum 10 GA steel, fully welded and constructed of heavy duty channel and gusseted in locations for safety and strength.
- Heavy duty oil and material vats and insulated firing chamber provide optimum fuel economy
- Full sweep, reciprocating, non-jamming agitation is hydraulically driven by a 6hp Kubota diesel engine.
- Diesel burner controlled by a digital Automatic Control System that controls oil and sealant temperatures.
- Easy to read rear mounted material and oil bi-metal thermometers are reliable and accurate requiring no electricity or wiring.
- Reverse loading material lids provide safe, anti-splash loading of material.
- Low center of gravity for safe towing, superior rear visibility and ease of operation.
- 2" material dispensing valve at rear of unit.
- 120V 1,500W Overnight heater(s) maintain heat to reduce daily start-up time.

SPECS

Models	UCMK130DT	UCMK230DT	UCMK370DT
Shipping Weight	3,045 lbs (1,381 kg)	4,116 lbs (1,867 kg)	5,287 lbs (2,398 kg)
Dimensions			
Overall Length	166"	187"	221"
Overall Width	80"	80"	80"
Overall Height	68"	72"	75″
Loading Height	50"	52"	55″
Capacity			
Material Vat	130 gal (492 L)	230 gal (870 L)	370 gal (1,399 L)
Heat Transfer Oil	35 gal (132 L)	50 gal (189 L)	69 gal (261 L)
Diesel Engine	6hp Kubota	6hp Kubota	6hp Kubota
Burner	(1) 340,000 BTU diesel burner	(1) 340,000 BTU diesel burner	(1) 340,000 BTU diesel burner
Suspension			
Axle(s)	Single	Tandem	Tandem
Capacity	5,200 lbs (3,182 kg)	10,400 lbs (4,717 kg)	10,400 lbs (4,717 kg)
Tires -size	(2) 225/75/R15	(4) 225/75/R15	(4) 225/75/R15

OPTIONS

- Hydraulic surge brakes
- 3" material dispensing valve
- Cone holder(s)
- Cone burning bracket extension(s)

*Specifications subject to change without notice.

- Green strobe burner indicator light
- Amber strobe light
- Flashing arrow stick with LED arrow ends
- Spare tire and rim mounted